(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 23 June 2005 (23.06.2005)

PCT

(10) International Publication Number WO 2005/056170 A1

(51) International Patent Classification7:

B01F 5/04

(21) International Application Number:

PCT/IB2004/002926

(22) International Filing Date:

9 September 2004 (09.09.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 2003/09466

5 December 2003 (05.12.2003) Z

(71) Applicant and

(72) Inventor: EWAN, Grant, Chapman [ZA/ZA]; No. 25 Segovia Logon Road, 2021 Bryanston (ZA).

(74) Agents: DONALD, Heather, June et al.; Spoor & Fisher, PO Box 41312, 2024 Craighall (ZA).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DOSING DEVICE



(57) Abstract: The invention concerns a dosing device (10) comprising a conduit (14) for conveying a main liquid stream. The conduit has a first inlet (16), an outlet (18) and a zone (20) of reduced cross-section between the inlet and outlet. A passage (42, 44) extends between the zone and atmosphere and there is a control valve (30) operable, when the main stream is to be to be dosed with a dosing liquid, to close the passage such that a relatively low pressure is generated in the zone when the main liquid stream flows from the first inlet to the outlet through the zone. There is a second inlet (22) through which the dosing liquid can be drawn into the low pressure zone to mix with the main liquid stream and form a mixed stream. In addition there is an aerator located in the conduit downstream of the venturi to receive air through the outlet and introduce it into the mixed stream.

